Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP480V55

External Battery Pack for Select 3-Phase UPS Systems

Highlights

- Extends runtime of modular series Tripp Lite UPS Systems using special +/- 240VDC configuration
- Hardwire installation
- Internal DC disconnect
- 10 year design lifespan

Description

Tripp Lite's BP480V55 External Battery Pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes internal disconnect for battery isolation.

Compatible UPS Systems: SU40K, SU60K, SU80K, SU20KX, SU40KX, SU60KX, SU80KX, SU60KTV and SU80KTV only.

Package Includes

- BP480V55 External Battery Pack
- Warranty information
- Owner's Manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS Systems
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- 10 year design lifespan

Specifications

BATTERY	
Expandable battery runtime	Multiple battery packs can be daisy-chained to the UPS for extended runtime
Connects to UPS via	Hardwire (contractor supplies wiring - see Owner's Manual for gauge recommendations)
DC system voltage	240VDC
Typical battery lifespan	10 year design lifespan
PHYSICAL	
Shipping weight (lbs)	2289
Shipping weight (kg)	1039
Unit weight (lbs)	2050
Unit weight (kg)	930.7
Unit Dimensions (HWD/in)	60 x 32.4 x 28.8
Unit Dimensions (HWD/cm)	152.4 x 82.3 x 73.2
Material of construction	Steel

Form factors supported	Tower
WARRANTY	
Product Warranty Period	1-year product warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3871.

©2009 Tripp Lite. All Rights Reserved.